



US LUBE®

Advance Technology • Superior Value

7/12/2023
6521G2VACOILREV0

US LUBE VACUUM PUMP OIL

Hydrotreated Industrial Oil formulated with highly refined Gp2 base stocks and specially selected additives designed to achieve premium performance that is suitable for mechanical vacuum pumps, particularly where good oil-water separation property, resistance to wear and oxidation, high viscosity index and long life service characteristics are required.

This product has a very narrow boiling spread and low volatility, as well as very low saturated steam pressure under high temperatures that guarantee high vacuum pressures are obtained.

Properties

- > Very low saturated steam pressure
- > High viscosity index
- > Resistance to wear
- > Outstanding long-term oxidation stability

Typical Specifications

Test Description	Method	Unit	ISO 68	ISO 100
ISO Viscosity Grade	-	-	ISO 68	ISO 100
Density @ 15 °C	ASTM D 4052	kg/L	0.886	0.885
Flash Point	ASTM D 92	°C	228	230
Pour Point	ASTM D 97	°C	-9	-9
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	68.2	98.1
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	8.7	11
Viscosity Index	ASTM D 2270	-	98	97

www.uslube-chicago.com

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranted of MERCHANTABILITY and FITNESS.

Ver 15/1