



**US LUBE**®

Advance Technology • Superior Value

11/6/2024  
GRIND-H2O-S2REV0

# US LUBE SHINEGRIND S2

This product is a biostable, fully synthetic grinding fluid with high levels of corrosion protection at low concentrations and possesses extremely good wheel flushing performance. Due to its unique formulation, it maintains a low foaming tendency and exhibits an ability to remain clean and clear in the presence of tramp oil.

This oil is free from Nitrites, Phenols, Chlorine and PTBBA and is developed for a wide variety of materials including cast iron, mild and stainless steels and non-ferrous materials.

When mixed with water, it gives a fluorescent green solution.

## Properties

---

- > Suitable for a wide variety of ferrous and non-ferrous metals
- > 3 - 5% dilution is suggested for general-purpose surface and cylindrical grinding
- > Contains preservative to protect product from fungi growth
- > Stable in water hardness between 50 and 350 ppm

## Typical Specifications

---

Test Description	Method	Unit	
Concentrate:			
Appearance	-	-	Fluorescent Green
Density @ 15 °C	ASTM D 4052	kg/L	1.0300

Test Description	Method	Unit	
Emulsion:			
Appearance	-	-	Fluorescent Green
pH @ 3%	-	-	9.3
IP 287 Corrosion Test %	-	-	2.5
Refractometer Factor	-	-	3.3

[www.uslube-chicago.com](http://www.uslube-chicago.com)

Furnishing the information contained herein does not constitute a representation by US Lube that any product or process is free from infringement claims of any third party nor does it constitute the granting of a license under any patent of US Lube or any third party. US Lube assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. US Lube warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.

Ver 15/1